

# ORDERING GUIDE

Item Code	Description	Luminaire Range	System Power Consumption (W)	Luminous Flux (lm)	Efficiency (lm/W)	UGR	SDCM	CRI	Average Rated Life (Hours - L80B50)	Width (mm)	Height (mm)
<b>OPTICLIP MODELS</b>											
<b>OPTICLIP RECESSED</b>											
0044003	OPTICLIP 600 4K C8 WH SSA WHITE	OptiClip Recessed	27	3300	122	17	3	80	60000	595	595
0044007	OPTICLIP 1200 4K C8 WH SSA WHITE	OptiClip Recessed	25	3100	124	19	3	80	60000	1195	1195
0044011	OPTICLIP 600 3K C8 WH SSA WHITE	OptiClip Recessed	27	3100	114	17	3	80	60000	595	595
0044015	OPTICLIP 1200 3K C8 WH SSA WHITE	OptiClip Recessed	27	3100	114	19	3	80	60000	1195	1195
0044019	OPTICLIP 600 4K C9 WH SSA WHITE	OptiClip Recessed	30	3275	109	17	3	90	60000	595	595
0044023	OPTICLIP 1200 4K C9 WH SSA WHITE	OptiClip Recessed	30	3250	108	20	3	90	60000	1195	1195

<b>OPTIX MODELS</b>											
<b>OPTIX LINEAR</b>											
0044960	OPTIX LIN R 1200 4K ALU SSA01	Optix Linear Recessed	27	3400	126	19	3	80	72000	95	1178
0044962	OPTIX LIN S 1200 4K ALU SSA01	Optix Linear Surface + Suspended	27	3400	126	19	3	80	72000	90	1165
0044964	OPTIX LIN S 1200 D/I 4K ALU SSA01	Optix Linear Surface + Suspended	32	3400	141	16	3	80	72000	90	1165
<b>OPTIX RECESSED</b>											
0044966	OPTIX R 600 2L 4K ALU SSA01	Optix Recessed	27	3400	126	16	3	80	72000	596	596
0044967	OPTIX R 600 2L 4K WHT SSA01	Optix Recessed	24	3400	142	19	3	80	72000	596	596
0044968	OPTIX R 600 2L SO 4K ALU SSA01	Optix Recessed	22	2800	127	16	3	80	72000	596	596
0044969	OPTIX R 600 2L SO 4K WHT SSA01	Optix Recessed	21	2850	136	19	3	80	72000	596	596
0044970	OPTIX R 600 3L HO 4K ALU SSA01	Optix Recessed	34	4500	132	16	3	80	72000	596	596
0044971	OPTIX R 600 3L HO 4K WHT SSA01	Optix Recessed	32	4450	139	19	3	80	72000	596	596
0044976	OPTIX R 1200 2L 4K ALU SSA01	Optix Recessed	27	3600	133	16	3	80	72000	296	1196
0044977	OPTIX R 1200 2L 4K WHT SSA01	Optix Recessed	25	3500	140	19	3	80	72000	296	1196
<b>OPTIX SURFACE + SUSPENDED</b>											
0044982	OPTIX S 1200 2L 4K ALU SSA01	Optix Surface + Suspended	27	3600	133	16	3	80	72000	200	1129
0044983	OPTIX S 1200 2L 4K WHT SSA01	Optix Surface + Suspended	24	3600	150	19	3	80	72000	200	1129
0044984	OPTIX S 1200 2L D/I 4K ALU SSA01	Optix Surface + Suspended	30	4100	137	16	3	80	72000	200	1129
0044985	OPTIX S 1200 2L D/I 4K WHT SSA01	Optix Surface + Suspended	26	4100	158	19	3	80	72000	200	1129
0044986	OPTIX S 1200 2L D/I HO 4K ALU SSA01	Optix Surface + Suspended	37	5600	151	16	3	80	72000	200	1129
0044987	OPTIX S 1200 2L D/I HO 4K WHT SSA01	Optix Surface + Suspended	36	5600	156	19	3	80	72000	200	1129
0044988	OPTIX S 1500 2L D/I HO 4K ALU SSA01	Optix Surface + Suspended	47	7000	149	14	3	80	72000	200	1410
0044989	OPTIX S 1500 2L D/I HO 4K WHT SSA01	Optix Surface + Suspended	42	7000	167	19	3	80	72000	200	1410

<b>RANA MODELS</b>											
<b>RANA LINEAR</b>											
0044911	RANA LINEAR R 3KLM WW LOUV+PRI SSA01	Rana Linear Recessed	28	2900	103	19	3	80	60000	90	1194
0044913	RANA LINEAR R 3KLM NW LOUV+PRI SSA01	Rana Linear Recessed	28	3050	108	19	3	80	60000	90	1194
0044915	RANA LINEAR R 3KLM WW MPO SSA01	Rana Linear Recessed	31	2900	93	21	3	80	60000	90	1194
0044917	RANA LINEAR R 3KLM NW MPO SSA01	Rana Linear Recessed	31	3100	100	21	3	80	60000	90	1194
0044919	RANA LINEAR R 3KLM WW OPAL SSA01	Rana Linear Recessed	32	3150	98	24	3	80	60000	90	1194
0044921	RANA LINEAR R 3KLM NW OPAL SSA01	Rana Linear Recessed	32	3300	103	24	3	80	60000	90	1194
0044923	RANA LINEAR S 3KLM WW LOUV+PRI SSA01	Rana Linear Surface + Suspended	28	2900	103	19	3	80	60000	87	1190
0044925	RANA LINEAR S 3KLM NW LOUV+PRI SSA01	Rana Linear Surface + Suspended	28	3050	108	19	3	80	60000	87	1190
0044927	RANA LINEAR S 3KLM WW MPO SSA01	Rana Linear Surface + Suspended	31	2900	93	21	3	80	60000	87	1190
0044929	RANA LINEAR S 3KLM NW MPO SSA01	Rana Linear Surface + Suspended	31	3100	100	21	3	80	60000	87	1190
0044931	RANA LINEAR S 3KLM WW OPAL SSA01	Rana Linear Surface + Suspended	32	3150	98	24	3	80	60000	87	1190
0044933	RANA LINEAR S 3KLM NW OPAL SSA01	Rana Linear Surface + Suspended	32	3300	103	24	3	80	60000	87	1190

# ORDERING GUIDE

Item Code	Description	Luminaire Range	System Power Consumption (W)	Luminous Flux (lm)	Efficiency (lm/W)	UGR	SDCM	CRI	Average Rated Life (Hours – L80B50)	Width (mm)	Height (mm)
<b>START PANEL MODELS</b>											
<b>START PANEL RECESSED</b>											
0042388	START PANEL UGR19 600X600 3800LM 830 SSA	START Panel Recessed	36	3800	106	19	3	80	50000	595	595
0042389	START PANEL UGR19 600X600 4000LM 840 SSA	START Panel Recessed	36	4000	111	19	3	80	50000	595	595
0042390	START PANEL UGR19 600X600 4600LM 830 SSA	START Panel Recessed	43	4600	107	19	3	80	50000	595	595
0042391	START PANEL UGR19 600X600 4800LM 840 SSA	START Panel Recessed	43	4800	112	19	3	80	50000	595	595
0042394	START PANEL UGR19 1200X300 3600LM 830 SSA	START Panel Recessed	36	3600	100	19	3	80	50000	295	1195
0042395	START PANEL UGR19 1200X300 3800LM 840 SSA	START Panel Recessed	36	3800	106	19	3	80	50000	295	1195

Item Code	Description	Accessory type	Power source	Width (mm)	Length (mm)	Height (mm)	Additional info
<b>ACCESSORY</b>							
0041538	EWBS SWITCH	Switch	Energy harvesting	81	81	14	Colour finish: White