

# SYLVANIA

## START eco Flood Flat

ST E STR FLD FLT IP65 15000LM 765 TR

0048959



### Product features

- Floodlight Led Luminaire, 150W 15000lm 30.000 H life.
- 3 year warranty. 6500K
- With motion bracket



## PRODUCT OVERVIEW

IPC Code	0048959
Product name	Floodlight Led Luminaire, 150W 15000lm
Technology	LED
Mounted	Surface
General application	Landscape lighting, Billboard lighting, Industrial and storage facilities
Certifications	CE EN 60598-2-5
ETIM Class	-----
Fixture luminous flux (lm)	15000lm
Luminaire efficacy (lm/W)	100lm/W
Colour temperature (K)	6500K
CRI (Ra)	>70
Photobiological Risk Group	Exempt Group 1
Total power consumption (W)	150W
Electrical protection	Class I
Dimmable	No
IP rating	IP65
IK rating	IK08
Product EAN number	5410288489599
Lamps	No

## DATA TABLE

### General data

IPC Code	0048959
Product name	Floodlight Led Luminaire, 150W 15000lm
Technology	LED
Mounted	Surface
General application	Landscape lighting, Billboard lighting, Industrial and storage facilities
Certifications	CE EN 60598-2-5
ETIM Class	-----



## START eco Flood Flat

ST E STR FLD FLT IP65 15000LM 765 TR

0048959

### Optical data

Fixture luminous flux (lm)	15000lm
Luminaire efficacy (lm/W)	100lm/W
Colour temperature (K)	6500K
Colour Code	765
CRI (Ra)	>70
Photobiological Risk Group	Exempt Group 1

### Electrical data

Total power consumption (W)	150W
Mains voltage (V)	220-240VAC
Electrical protection	Class I
Dimmable	No
Drive current (mA)	-
Nominal Frequency (Hz)	50/60Hz

### Lifetime data

Lumen maintenance - L70	-
-------------------------	---

### Physical data

IP rating	IP65
IK rating	IK08
Nominal Product Length (mm)	255
Nominal Product Width (mm)	345
Nominal Product Height (mm)	34
Weight (kg)	2,1

### Packaging

Single packaging type	Carton
Product EAN number	5410288489599
Packaging single length / height (mm)	378
Packaging single width (mm)	304
Packaging single depth (mm)	49
Units per inner package	1
DUN14 (outer)	-
Units per outer package	6
Packaging outer length / height (mm)	318
Packaging outer width (mm)	330
Packaging outer depth (mm)	393