

Concord
by SYLVANIA Group







LumiNature

LumiNature Product list



Digital | Lighting | Solutions

Solstice

IMAGE	ITEM CODE	DESCRIPTION	CONTROL TECHNOLOGY	COLOUR TEMPERATURE (K)	SYSTEM POWER CONSUMPTION (W)	LUMINOUS FLUX (LM)	LUMINANCE (CD/M ² @65DEGREE)	MELANOPIC RATIO /MEER	FIDELITY INDEX R	GAMUT INDEX R	CRI	UGR
SOLSTICE LUMINATURE  RECESSED DOWNLIGHT												
	2070141	SOLSTICE 150 1450LM LUMI 930 DALI	DALI	3000K	17	1450	<150	0,609	97	101	97	<19
	2070142	SOLSTICE 150 1550LM LUMI 940 DALI	DALI	4000K	17	1550	<150	0,801	95	98	97	<19
	2070143	SOLSTICE 150 1450LM LUMI 930 SSC	SylSmart Standalone	3000K	17	1450	<150	0,609	97	101	97	<19
	2070144	SOLSTICE 150 1550LM LUMI 940 SSC	SylSmart Standalone	4000K	17	1550	<150	0,801	95	98	97	<19
	2070160	SOLSTICE 200 1800LM LUMI 930 DALI	DALI	3000K	18	1800	<300	0,619	97	102	97	<19
	2070161	SOLSTICE 200 1900LM LUMI 940 DALI	DALI	4000K	18	1900	<300	0,817	94	98	97	<19
	2070162	SOLSTICE 200 1800LM LUMI 930 SSC	SylSmart Standalone	3000K	18	1800	<300	0,619	97	102	97	<19
	2070163	SOLSTICE 200 1900LM LUMI 940 SSC	SylSmart Standalone	4000K	18	1900	<300	0,817	94	98	97	<19
	SOLSTICE LUMINATURE HCL TUNABLE WHITE  RECESSED DOWNLIGHT											
	2070145	SOLSTICE 150 LUMI HCL TW SSC	SylSmart Standalone	2700K	23	1580	<300	0,503	97	102	97	<19
	SylSmart Standalone		4000K	23	1830	<300	0,85	96	102	94	<19	
	SylSmart Standalone		6500K	23	1845	<300	1,114	97	100	99	<19	
	2070164	SOLSTICE 200 LUMI HCL TW SSC	SylSmart Standalone	2700K	23	1840	<300	0,517	97	102	97	<19
	SylSmart Standalone		4000K	23	2050	<300	0,868	95	102	93	<19	
	SylSmart Standalone		6500K	23	2120	<300	1,141	95	99	97	<19	

Equinox













IMAGE	ITEM CODE	DESCRIPTION	CONTROL TECHNOLOGY	COLOUR TEMPERATURE (K)	SYSTEM POWER CONSUMPTION (W)	LUMINOUS FLUX (LM)	LUMINANCE (CD/M ² @65DEGREE)	MELANOPIC RATIO /MEER	FIDELITY INDEX R	GAMUT INDEX R	CRI	UGR
EQUINOX LUMINATURE HCL TUNABLE WHITE  RECESSED DOWNLIGHT												
 	2059953	EQUINOX 165 1975 LUMI HCL TW SSC WHITE	SylSmart Standalone	2700K	25	1823	<3100	0,52	93	103	97	<19
			SylSmart Standalone	4000K	25	1975	<3100	0,86	95	102	97	<19
			SylSmart Standalone	6500K	25	2144	<3100	1,14	96	100	98	<19
	2059961	EQUINOX 165 1925 LUMI HCL TW SSC BLACK	SylSmart Standalone	2700K	25	1815	<3000	0,52	95	103	97	<19
			SylSmart Standalone	4000K	25	1925	<3000	0,87	95	102	93	<19
			SylSmart Standalone	6500K	25	2110	<3000	1,15	96	99	97	<19

IMAGE	ITEM CODE	DESCRIPTION	CONTROL TECHNOLOGY	COLOUR TEMPERATURE (K)	SYSTEM POWER CONSUMPTION (W)	LUMINOUS FLUX (LM)	LUMINANCE (CD/M2 @65DEGREE)	MELANOPIC RATIO /MEER	MELANOPIC RATIO /MDER	FIDELITY INDEX R	GAMUT INDEX R	FIDELITY INDEX (SKIN)	CRI	UGR
	OTPIX LUMINATURE 4000K RECESSED*													
	2023832	OPTIX RECESSED 600 2L LUMI 4K ALU	Switch	4000K	30	2 915	<200	0,77	0,70	94	98	94	98	<16
	2023833	OPTIX RECESSED 600 2L LUMI 4K ALU DALI	DALI	4000K	30	2 915	<200	0,77	0,70	94	98	94	98	<16
	2023941	OPTIX RECESSED 600 2L LUMI 4K ALU SSA	SylSmart Connected	4000K	31	2 915	<200	0,77	0,70	94	98	94	98	<16
	2023834	OPTIX RECESSED 600 2L LUMI 4K ALU SSC	SylSmart Standalone	4000K	31	2 915	<200	0,77	0,70	94	98	94	98	<16
	2023842	OPTIX RECESSED 600 3L LUMI 4K ALU	Switch	4000K	37	3 750	<200	0,78	0,71	94	98	94	98	<16
	2023843	OPTIX RECESSED 600 3L LUMI 4K ALU DALI	DALI	4000K	37	3 750	<200	0,78	0,71	94	98	94	98	<16
	2023943	OPTIX RECESSED 600 3L LUMI 4K ALU SSA	SylSmart Connected	4000K	38	3 750	<200	0,78	0,71	94	98	94	98	<16
	2023844	OPTIX RECESSED 600 3L LUMI 4K ALU SSC	SylSmart Standalone	4000K	38	3 750	<200	0,78	0,71	94	98	94	98	<16
	2023837	OPTIX RECESSED 1200 2L LUMI 4K ALU	Switch	4000K	36	3 810	<200	0,78	0,71	93	98	93	98	<16
	2023838	OPTIX RECESSED 1200 2L LUMI 4K ALU DALI	DALI	4000K	36	3 810	<200	0,78	0,71	93	98	93	98	<16
	2023942	OPTIX RECESSED 1200 2L LUMI 4K ALU SSA	SylSmart Connected	4000K	37	3 810	<200	0,78	0,71	93	98	93	98	<16
	2023839	OPTIX RECESSED 1200 2L LUMI 4K ALU SSC	SylSmart Standalone	4000K	37	3 810	<200	0,78	0,71	93	98	93	98	<16
	OTPIX LUMINATURE 4000K SURFACE*													
	2023827	OPTIX SURFACE 1200 2L LUMI 4K ALU	Switch	4000K	36	3 810	<200	0,78	0,71	93	98	93	98	<16
	2023828	OPTIX SURFACE 1200 2L LUMI 4K ALU DALI	DALI	4000K	36	3 810	<200	0,78	0,71	93	98	93	98	<16
	2023940	OPTIX SURFACE 1200 2L LUMI 4K ALU SSA	SylSmart Connected	4000K	37	3 810	<200	0,78	0,71	93	98	93	98	<16
	2023829	OPTIX SURFACE 1200 2L LUMI 4K ALU SSC	SylSmart Standalone	4000K	37	3 810	<200	0,78	0,71	93	98	93	98	<16
	OTPIX LUMINATURE 4000K LINEAR RECESSED													
	2023847	OPTIX LINEAR RECESSED 1200 LUMI 4K ALU	Switch	4000K	30	2 870	<200	0,78	0,71	94	98	94	98	<19
	2023848	OPTIX LINEAR RECESSED 1200 LUMI 4K ALU DALI	DALI	4000K	30	2 870	<200	0,78	0,71	94	98	94	98	<19
	2023944	OPTIX LINEAR RECESSED 1200 LUMI 4K ALU SSA	SylSmart Connected	4000K	31	2 870	<200	0,78	0,71	94	98	94	98	<19
	2023849	OPTIX LINEAR RECESSED 1200 LUMI 4K ALU SSC	SylSmart Standalone	4000K	31	2 870	<200	0,78	0,71	94	98	94	98	<19
	OTPIX LUMINATURE 4000K LINEAR SURFACE													
	2023852	OPTIX LINEAR SURFACE 1200 LUMI 4K ALU	Switch	4000K	30	2 870	<200	0,78	0,71	94	98	94	98	<19
	2023853	OPTIX LINEAR SURFACE 1200 LUMI 4K ALU DALI	DALI	4000K	30	2 870	<200	0,78	0,71	94	98	94	98	<19
	2023945	OPTIX LINEAR SURFACE 1200 LUMI 4K ALU SSA	SylSmart Connected	4000K	31	2 870	<200	0,78	0,71	94	98	94	98	<19
	2023854	OPTIX LINEAR SURFACE 1200 LUMI 4K ALU SSC	SylSmart Standalone	4000K	31	2 870	<200	0,78	0,71	94	98	94	98	<19
	2023857	OPTIX LINEAR SURFACE 1200 DI LUMI 4K ALU	Switch	4000K	36	4 020	<200	0,78	0,71	93	98	93	98	<16
	2023858	OPTIX LINEAR SURFACE 1200 DI LUMI 4K ALU DALI	DALI	4000K	36	4 020	<200	0,78	0,71	93	98	93	98	<16
	2023946	OPTIX LINEAR SURFACE 1200 DI LUMI 4K ALU SSA	SylSmart Connected	4000K	37	4 020	<200	0,78	0,71	93	98	93	98	<16
	2023859	OPTIX LINEAR SURFACE 1200 DI LUMI 4K ALU SSC	SylSmart Standalone	4000K	37	4 020	<200	0,78	0,71	93	98	93	98	<16

* 625x625mm and 4 LED lines versions available on request

IMAGE	ITEM CODE	DESCRIPTION	CONTROL TECHNOLOGY	COLOUR TEMPERATURE (K)	SYSTEM POWER CONSUMPTION (W)	LUMINOUS FLUX (LM)	LUMINANCE (CD/M2 @65DEGREE)	MELANOPIC RATIO /MEER	MELANOPIC RATIO /MDER	FIDELITY INDEX R	GAMUT INDEX R	FIDELITY INDEX (SKIN)	CRI	UGR
OPTIX LUMINATURE HCL TUNABLE WHITE   RECESSED*														
	2023835	OPTIX RECESSED 600 2L LUMI HCL TW ALU DALI	DALI DT8	2800K	32	2 280	<200	0,53	0,48	97	103	99	98	<16
4000K				32	2 780	<200	0,82	0,74	95	101	95	96	<16	
6200K				32	2 690	<200	1,08	0,98	96	99	97	99	<16	
	2023836	OPTIX RECESSED 600 2L LUMI HCL TW ALU SSC	SylSmart Standalone	2800K	33	2 280	<200	0,53	0,48	97	103	99	98	<16
SylSmart Standalone			4000K	33	2 780	<200	0,82	0,74	95	101	95	96	<16	
SylSmart Standalone			6200K	33	2 690	<200	1,08	0,98	96	99	97	99	<16	
	2023845	OPTIX RECESSED 600 3L LUMI HCL TW ALU DALI	DALI DT8	2800K	37	2 930	<200	0,53	0,48	97	101	99	98	<16
4000K				37	3 510	<200	0,82	0,74	95	101	95	96	<16	
6200K				37	3 410	<200	1,08	0,98	96	99	97	99	<16	
	2023846	OPTIX RECESSED 600 3L LUMI HCL TW ALU SSC	SylSmart Standalone	2800K	38	2 930	<200	0,53	0,48	97	101	99	98	<16
SylSmart Standalone			4000K	38	3 510	<200	0,82	0,74	95	101	95	96	<16	
SylSmart Standalone			6200K	38	3 410	<200	1,08	0,98	96	99	97	99	<16	
	2023840	OPTIX RECESSED 1200 2L LUMI HCL TW ALU DALI	DALI DT8	2800K	36	2 900	<200	0,52	0,47	97	101	98	98	<16
4000K				36	3 500	<200	0,82	0,74	94	101	94	95	<16	
6200K				36	3 480	<200	1,07	0,97	95	99	96	98	<16	
	2023841	OPTIX RECESSED 1200 2L LUMI HCL TW ALU SSC	SylSmart Standalone	2800K	37	2 900	<200	0,52	0,47	97	101	98	98	<16
SylSmart Standalone			4000K	37	3 500	<200	0,82	0,74	94	101	94	95	<16	
SylSmart Standalone			6200K	37	3 480	<200	1,07	0,97	95	99	96	98	<16	
OPTIX LUMINATURE HCL TUNABLE WHITE   SURFACE*														
	2023830	OPTIX SURFACE 1200 2L LUMI HCL TW ALU DALI	DALI DT8	2800K	36	2 900	<200	0,52	0,48	97	101	98	98	<16
4000K				36	3 500	<200	0,82	0,74	94	101	94	95	<16	
6200K				36	3 480	<200	1,07	0,97	95	99	96	98	<16	
	2023831	OPTIX SURFACE 1200 2L LUMI HCL TW ALU SSC	SylSmart Standalone	2800K	37	2 900	<200	0,52	0,48	97	101	98	98	<16
SylSmart Standalone			4000K	37	3 500	<200	0,82	0,74	94	101	94	95	<16	
SylSmart Standalone			6200K	37	3 480	<200	1,07	0,97	95	99	96	98	<16	

* 625x625mm and 4 LED lines versions available on request

IMAGE	ITEM CODE	DESCRIPTION	CONTROL TECHNOLOGY	COLOUR TEMPERATURE (K)	SYSTEM POWER CONSUMPTION (W)	LUMINOUS FLUX (LM)	LUMINANCE (CD/M2 @65DEGREE)	MELANOPIC RATIO /MEER	MELANOPIC RATIO /MDER	FIDELITY INDEX R	GAMUT INDEX R	FIDELITY INDEX (SKIN)	CRI	UGR
OPTIX LUMINATURE HCL TUNABLE WHITE   LINEAR RECESSED														
	2023850	OPTIX LINEAR RECESSED 1200 LUMI HCL TW ALU DA	DALI DT8	2800K	26	1 850	<200	0,53	0,48	97	102	99	98	<16
				4000K	26	2 200	<200	0,83	0,75	95	101	95	95	<16
				6200K	26	2 180	<200	1,09	0,99	96	99	96	98	<16
	2023851	OPTIX LINEAR RECESSED 1200 LUMI HCL TW ALU SSC	SylSmart Standalone	2800K	27	1 850	<200	0,53	0,48	97	102	99	98	<16
				4000K	27	2 200	<200	0,83	0,75	95	101	95	95	<16
				6200K	27	2 180	<200	1,09	0,99	96	99	96	98	<16
OPTIX LUMINATURE HCL TUNABLE WHITE   LINEAR SURFACE														
	2023855	OPTIX LINEAR SURFACE 1200 LUMI HCL TW ALU DALI	DALI DT8	2800K	26	1 850	<200	0,53	0,48	97	102	99	98	<16
				4000K	26	2 200	<200	0,83	0,75	95	101	95	95	<16
				6200K	26	2 180	<200	1,09	0,99	96	99	96	98	<16
	2023856	OPTIX LINEAR SURFACE 1200 LUMI HCL TW ALU SSC	SylSmart Standalone	2800K	27	1 850	<200	0,53	0,48	97	102	99	98	<16
				4000K	27	2 200	<200	0,83	0,75	95	101	95	95	<16
				6200K	27	2 180	<200	1,09	0,99	96	99	96	98	<16
	2023860	OPTIX LINEAR SURFACE 1200 DI LUMI HCL TW ALU DALI	DALI DT8	2800K	38	2 860	<200	0,52	0,47	91	101	99	98	<16
				4000K	38	3 540	<200	0,82	0,74	95	101	95	96	<16
				6200K	38	3 490	<200	1,08	0,98	96	99	96	98	<16
2023861	OPTIX LINEAR SURFACE 1200 DI LUMI HCL TW ALU SSC	SylSmart Standalone	2800K	39	2 860	<200	0,52	0,47	91	101	99	98	<16	
			4000K	39	3 540	<200	0,82	0,74	95	101	95	96	<16	
			6200K	39	3 490	<200	1,08	0,98	96	99	96	98	<16	